

CHEMLUBE® NGBR SERIES

NATURAL GAS COMPRESSOR LUBRICANTS

Applications:

Chemlube NGBR Series are fully synthetic lubricants formulated for smaller booster or recovery compressors, using superior synthetic base stocks and select additives. They are superior to conventional petroleum-based oils and will inhibit the formation of varnish and carbon build-up. Chemlube NGBR 20W and 30W allow for extended equipment life and decrease lubricant drain intervals, reducing the waste oil disposal costs and extending equipment life.

Typical Industrial Applications:

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Reciprocating Compressors

Performance Benefits:

- Excellent film strength
- Compatibility with most base oils
- Excellent oxidative stability
- Reduced maintenance costs
- Extended equipment life and drain intervals

TYPICAL PROPERTIES	TEST METHOD	Chemlube NGBR 20W	Chemlube NGBR 30W
ISO Grade	ASTM D2422	46	100
Viscosity @ 40°C,cSt	ASTM D445	50.0	96.9
Viscosity @ 100°C,cSt	ASTM D445	8.75	13.4
Viscosity Index	ASTM D2270	154	139
Flash Point, °C/°F	ASTM D92	253/489	248/479
Pour Point, °C/°F	ASTM D97	-49/-56	-49/-56
Specific Gravity	ASTM D1298	0.88	0.88

CHEMLUBE®

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com